



Industrial Automation Products & Solutions



Belden 9223 Series, 152.4m, RG58 Coaxial, Unterminated 50 Ω

ผู้ผลิต : Belden

รหัสสินค้า : 9223 010500

Specifications

คุณลักษณะ	รายละเอียด
Terminated/Unterminated	Unterminated
Coaxial Type	RG58
Outer Diameter	4.826mm
CPR Certification	Eca
Characteristic Impedance	50 Ω
Attenuation	0.476 dB @ 1000 MHz
Length	152.4m
Sheath Colour	Black
Voltage Rating	1.9 kV ac
Conductor Strand Type	Stranded
Series	9223
Number of Strands	7
Operating Temperature Range	-40 - +80 °C
Shielding	Tinned Copper Braid
Capacitance	121.3pF/m
Sheath Material	Polyvinyl Chloride PVC
Insulation Material	PE
Core Strands	7/0.73



บริษัท ทีเอส โซลูชั่น จำกัด

27/66 ถนนรัชดา-รามอินทรา แขวงรามอินทรา เขตคันนายาว กรุงเทพมหานคร 10230

โทร : 02-066-1996 | Line OA : @thsolution | www.thsolution.com

Maximum Operating Temperature	+80°C
Velocity ratio	56%
Minimum Operating Temperature	-40°C
Size of Strands	22 AWG
Conductor Material	Tinned Copper
Standards Met	CPR Euroclass:Eca, EU Directive 2000/53/EC (ELV), EU Directive 2003/11/EC (BFR), EU Directive 2011/65/EU (ROHS II), EU Directive 2012/19/EU (WEEE), EU Directive 2015/863/EU, EU Directive Compliance:EU Directive 2003/11/EC (BFR)



LINE OA
@thsolution

Need a quotation or technical support?

ติดต่อทีมงาน THSolution สำหรับข้อมูลสินค้า ราคา สต็อกสินค้า

Tel. : 02-066-1996

LINE OA : @thsolution

Website : www.thsolution.com